

APPLICATIONS	Heating, Cooling, Steam applications
MAX. FLOWRATE	600 m ³ /h (with water)
MAX. NUMBER OF PLATES	389
FRAME	PN10, PN16 (standard PN16) on request PN25

MATERIALS	FRAME	Painted carbon steel Stainless steel AISI 304 – AISI 316
	PLATES	Stainless steel AISI 304 – AISI 316 titanium, incoloy, monel, hastelloy
	GASKETS	NBR, EPDM, EPM, FKM, Silicone
	CONNECTIONS	Carbon steel, stainless steel

DIMENSIONS

NOMINAL PRESSURE	PN10	PN16
A	763	773
B	396	396
C	1367	1367
D	776	776
F	N° of plates x 3,10	N° of plates x 3,10
G	DN200	DN200
H	262,5	262,5
S1 / S2	45 / 40	60 / 50
unit. surface (m ²)	0,4025	0,4025
Channel Vol. (l)	1,274	1,274
Plate weight (Kg)	2,4	2,4
Plate thickness (mm)	0,5	0,6
Frame weight (Kg)	730	930
Boltings	N°8 M30 + N°4 M30	N°8 M36x3 + N°4 M30

N°OF PLATES	93	139	185	231	277	325
E	710	960	1210	1460	1710	1960

DIMENSIONS

